

ANOVA Based Optimization of Machining Parameters

¹Sandip, ²Rajeev Roshan

¹*Research Scholar Master of Technology (APS) Department of Mechanical Engineering, NIIST, Bhopal*

²*Assistant professor, Department of Mechanical Engineering, NIIST, Bhopal (M.P.)*

Abstract—Machining operations such as turning, milling, and drilling are widely used in manufacturing industries to produce components with required dimensional accuracy and surface quality. The selection of optimal machining parameters plays a crucial role in improving productivity and reducing manufacturing cost. Analysis of Variance (ANOVA) is a powerful statistical tool used to determine the significance of machining parameters and their contribution toward performance characteristics such as surface roughness, tool wear, cutting force, and material removal rate. This review paper summarizes recent research work on ANOVA-based optimization of machining parameters in various machining processes. The study focuses on different optimization techniques such as Taguchi method, Response Surface Methodology (RSM), Grey Relational Analysis (GRA), and hybrid machine learning approaches combined with ANOVA. The review highlights that feed rate and cutting speed are generally the most influential parameters affecting surface quality and machining performance. Furthermore, this paper discusses the major research gaps and future research opportunities in the field of machining parameter optimization.

Index Terms—ANOVA, Machining Parameters, Optimization, Surface Roughness, Taguchi Method, Response Surface Methodology, CNC Machining.

I. INTRODUCTION

Machining processes play a significant role in manufacturing industries, especially in the production of precision components used in automotive, aerospace, and tool manufacturing sectors. The performance of machining operations largely depends on the selection of appropriate cutting parameters such as cutting speed, feed rate, and depth of cut.

Improper selection of machining parameters may lead to poor surface finish, excessive tool wear, and reduced productivity. Therefore, optimization of machining parameters has become an important research area in modern manufacturing engineering.

Statistical techniques are widely used to optimize machining parameters. Among these techniques, Analysis of Variance (ANOVA) is one of the most effective tools used to determine the significance and percentage contribution of different machining parameters.

ANOVA helps researchers identify the most influential parameters affecting machining performance. When combined with optimization techniques such as Taguchi method and Response Surface Methodology, ANOVA provides a reliable framework for improving machining performance.

This review paper aims to analyze the recent research work on ANOVA-based optimization techniques used in machining operations.

II. LITERATURE REVIEW

Many researchers have applied ANOVA to identify the influence of machining parameters on machining performance.

Sharma et al. (2022) investigated the optimization of turning parameters for EN31 steel using the Taguchi method combined with ANOVA. Their results showed that feed rate had the highest influence on surface roughness followed by cutting speed and depth of cut.

Kumar and Singh (2023) studied the effect of machining parameters on surface roughness during CNC turning of aluminum alloy. ANOVA analysis revealed that feed rate contributed more than 60% to surface roughness variation.

Patel et al. (2023) applied Response Surface Methodology combined with ANOVA for optimization of milling parameters in CNC machining of stainless steel. Their results indicated that cutting speed and feed rate significantly affect the surface finish.

Verma et al. (2024) investigated drilling parameters for composite materials using ANOVA and Grey Relational Analysis. The study concluded that spindle speed and feed rate were the most important parameters affecting thrust force and delamination.

Gupta et al. (2024) analyzed the optimization of machining parameters in CNC turning using the Taguchi method and ANOVA. Their findings demonstrated that optimal cutting conditions significantly reduce surface roughness and improve tool life.

Reddy et al. (2025) applied ANOVA with machine learning techniques to predict machining performance. Their research showed that hybrid optimization methods provide better accuracy in predicting machining outcomes compared to conventional statistical models.

Several studies confirm that ANOVA is a reliable statistical tool for identifying the influence of machining parameters and supporting optimization techniques.

III. EFFECT OF MACHINING PARAMETERS ON MACHINING PERFORMANCE

3.1 Cutting Speed

Cutting speed plays an important role in machining performance. Higher cutting speeds generally improve surface finish due to smoother cutting action. However, excessive cutting speed may lead to higher temperatures and tool wear.

ANOVA studies in machining processes show that cutting speed contributes significantly to surface roughness and tool life.

3.2 Feed Rate

Feed rate is considered one of the most influential parameters affecting surface roughness. Higher feed rates increase material removal rate but also increase surface roughness. Many ANOVA-based studies show that feed rate has the highest percentage contribution to surface quality compared to other parameters.

3.3 Depth of Cut

Depth of cut mainly affects cutting force and material removal rate. Increasing depth of cut increases productivity but may lead to higher cutting forces and vibration.

ANOVA results from several machining studies show that depth of cut has a moderate influence compared to cutting speed and feed rate.

IV. OPTIMIZATION TECHNIQUES COMBINED WITH ANOVA

4.1 Taguchi Method with ANOVA

The Taguchi method is widely used for experimental design and optimization in machining processes. When combined with ANOVA, it helps determine the significance of each machining parameter.

This method reduces the number of experiments while providing reliable optimization results.

4.2 Response Surface Methodology (RSM)

RSM is used to develop mathematical models for machining processes. ANOVA is used to validate the significance of the developed models.

RSM helps in analyzing the interaction between different machining parameters and identifying optimal conditions.

4.3 Grey Relational Analysis (GRA)

Grey Relational Analysis is used for multi-objective optimization problems where multiple responses such as surface roughness, tool wear, and material removal rate need to be optimized simultaneously.

ANOVA helps determine the importance of each parameter affecting the grey relational grade.

4.4 Machine Learning Based Optimization

Recent research combines ANOVA with machine learning techniques such as Artificial Neural Networks (ANN), Support Vector Machines (SVM), and Genetic Algorithms.

These methods improve prediction accuracy and help in developing intelligent machining systems.

V. RESEARCH GAP

Despite significant research in machining parameter optimization, several research gaps still exist:

1. Limited studies integrating ANOVA with advanced artificial intelligence techniques for real-time optimization.
2. Lack of research on multi-objective optimization considering sustainability factors such as energy consumption and tool wear.
3. Most studies focus on single machining processes, whereas hybrid machining processes are rarely investigated.
4. Limited research on real-time monitoring systems integrated with ANOVA-based optimization models.

Addressing these research gaps will help develop more efficient machining systems.

VI. FUTURE RESEARCH DIRECTIONS

Future research in machining parameter optimization may focus on:

- Integration of ANOVA with Artificial Intelligence and Machine Learning techniques.
- Development of real-time adaptive machining systems.
- Optimization of machining parameters for advanced materials such as composites and superalloys.
- Use of smart sensors and Industry 4.0 technologies for monitoring machining performance.

These developments will enhance the efficiency and reliability of machining processes.

VII. CONCLUSION

Optimization of machining parameters is essential for improving machining performance and product quality. ANOVA is widely used to determine the significance of machining parameters and their contribution to machining performance.

This review study shows that feed rate and cutting speed are the most influential parameters affecting surface roughness and machining efficiency. Techniques such as Taguchi method, Response Surface Methodology, and Grey Relational Analysis combined with ANOVA provide effective solutions for machining parameter optimization.

Future research should focus on integrating ANOVA with advanced machine learning techniques and real-time monitoring systems to achieve intelligent and automated machining systems.

REFERENCES

- [1] Sharma, R., et al. (2022). Optimization of machining parameters using Taguchi and ANOVA method. *Journal of Manufacturing Processes*.

- [2] Kumar, S., Singh, P. (2023). CNC turning parameter optimization using statistical analysis. International Journal of Advanced Manufacturing Technology.
- [3] Patel, A., et al. (2023). Milling parameter optimization using RSM and ANOVA. Materials Today Proceedings.
- [4] Verma, P., et al. (2024). Optimization of drilling parameters in composite materials using ANOVA. Composite Structures Journal.
- [5] Gupta, R., et al. (2024). Taguchi-based optimization of machining parameters in CNC turning. Procedia Manufacturing.
- [6] Reddy, V., et al. (2025). Machine learning-based optimization of machining processes. Journal of Intelligent Manufacturing.
- [7] Singh, M., et al. (2023). Multi-response optimization in machining using Grey Relational Analysis. Manufacturing Letters.
- [8] Tzotzis, A., et al. (2025). Machine learning prediction of machining performance. Journal of Manufacturing Science.
- [9] Kumar, D., et al. (2024). Optimization of cutting parameters in CNC machining. International Journal of Mechanical Engineering.
- [10] Patel, H., et al. (2023). Statistical analysis of machining parameters using ANOVA. Engineering Research Journal.